



TQX.11007 Triple QX Motor Oil 5W-30 SYNPLUS LL
III

Document version: 6 Sep 2026



Description	TRIPLE QX SYNPLUS VAG 5W30 SYNTHETIC is designed for VAG engines where the VW 504.00/ 507.00 specification is required. It is also designed to meet specifications of other OEM's and reaches ACEA and API requirements by balancing excellent fluidity with advanced engine protection, regardless of the driving conditions.			
According to the specifications of	ACEA C3 API SN BMW Longlife-04 MB 229.51 / 229.52 Opel OV 040 1547 - D30 Porsche C30 VW 504.00 / 507.00			
Packaging units	ART. NR.	VOLUME	ITEMS PER UNIT	ITEMS PER PALLET
	TQX.521776092	1 L	12	-
	TQX.521776091	5 L	4	-
	TQX.521776095	20 L	1	-
	TQX.521776099	60 L	1	-
	TQX.521771656	199 L	1	-

Standard analyses

TEST	VALUE		METHOD
Density at 15°C	0.856	kg/l	ASTM D4052
Kinematic Viscosity at 40°C	68.0	mm2/s	ASTM D445
Kinematic Viscosity at 100°C	11.7	mm2/s	ASTM D445
Viscosity Index	169		ASTM D2270
Flashpoint COC	230	°C	ASTM D92
Pourpoint	-39	°C	ASTM D6892
Total Base Number	8.3	mgKOH/g	ASTM D2896
Sulphated Ash	0.7	mass%	ASTM D874

These characteristics are typical of current production. Variations in these characteristics may occur.